

DIRECTLIGHT®

Économisez . Créez . Optimisez .

FICHE TECHNIQUE



TUBE LED T8

⇒ 0,60m / 1,20 m / 1,50 m


REFERENCE	PUISSANCE	CCT (K)	FLUX	CRI	ANGLE	CAPOT
IC-T8C30-BJ	30	4000	3450 lm	>80	120°	CLAIR
IC-T8F30-BJ	30	4000	3150 lm	>80	120°	OPAQUE
IC-T8C24-BJ	24	4000	2520 lm	>80	120°	CLAIR
IC-T8F24-BJ	24	4000	2280 lm	>80	120°	OPAQUE
IC-T8C20-BJ	20	4000	1900 lm	>80	120°	CLAIR
IC-T8F20-BJ	20	4000	2100 lm	>80	120°	OPAQUE
IC-T8C17-BJ	17	4000	1615 lm	>80	120°	CLAIR
IC-T8F17-BJ	17	4000	1785 lm	>80	120°	OPAQUE
IC-T8C11-BJ	11	4000	1045 lm	>80	120°	CLAIR
IC-T8F11-BJ	11	4000	1155 lm	>80	120°	OPAQUE

Teddy Guérin

Mob: +33 6 48 99 04 50

N° TN : 55 105 481

Email: tguerin@direct-light.fr



www.direct-light.fr

